


**BICO SPRAY CONE OCO DE LINHA****MODELO
CO5**

Código	Conexão BSP/NPT	Vazão l/min												Ângulo de Aspersão			A mm
		Pressão kg/cm2												0.5	1.5	6	
		0.2	0.5	0.7	1	1.5	2	3	4	5	6	7					
3	3/8"		1	1.1	1.3	1.7	2.0	2.3	2.7	3	3.3	3.6	51	64	76	33	
5		1	1.6	1.9	2.3	2.8	3.3	3.9	4.5	5.2	5.6	6	56	67	75		
8		1.6	2.6	3.3	3.6	4.4	5.2	6.3	7.2	8.2	9	9.6	56	65	70		
10		2.0	3.2	3.8	4.6	5.6	6.4	7.9	9.1	10.2	11.2	12	55	65	72		
14		4.5	5.3	6.3	7.7	8.9	11	12.7	14.2	15.5	16.8	61	65	67			
5	1/2"	1.0	1.6	1.9	2.3	2.8	3.3	4.0	4.5	5.1	5.6	6.0	63	65	67	39	
8		1.6	2.6	3.1	3.6	4.5	5.2	6.3	7.3	8.3	8.9	9.5	61	69	73		
10		2.0	3.2	3.8	4.5	5.5	6.4	7.8	9.0	10	11	12	64	70	74		
15		3.1	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	16.7	18	60	67	70		
20		4.0	6.4	7.6	9.0	11	12.8	15.7	18	20	22	24	63	65	69		
25		5.1	8.1	9.5	11.5	14	16	20	23	25	28	30	59	63	68	46	
5	3/4"	1.0	1.6	1.9	2.3	2.8	3.3	4.0	4.5	5.1	5.6	6.0	63	65	67		
8		1.6	2.6	3.1	3.6	4.5	5.2	6.3	7.3	8.3	8.9	9.5	61	69	73		
10		2.0	3.2	3.8	4.5	5.5	6.4	7.8	9.0	10	11	12	64	70	74		
15		3.1	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	16.7	18	60	67	70		
20		4.0	6.4	7.6	9.0	11	12.8	15.7	18	20	22	24	63	65	69		
25		5.1	8.1	9.5	11.5	14	16	20	23	25	28	30	59	63	68	68	
50		10.2	16	19	23	28	32	39	46	51	57	61	70	73	74		
40	1 1/2"	8.2	13	15	18	22	26	32	36	41	45	48	70	73	74		
50		10	16	19	23	28	32	39	45	51	55	60	72	75	77		
60		12	19	23	27	33	39	47	55	61	67	72	74	76	79		
70		14	23	27	32	39	45	55	64	71	78	85	76	79	83		
80		16	26	30	36	44	51	63	72	81	89	96	78	82	84		
90		18	29	34	41	50	58	71	82	90	101	110	81	84	84		
100		20	32	38	45	55	64	78	90	100	110	120	83	86	86		
110		22	35	42	50	61	70	86	100	111	122	132	85	88	88		
120		24	39	46	55	67	77	95	109	122	134	145	87	90	90		

MATERIAL: LATÃO - INOX - Outros materiais sob consulta.**EXEMPLO PARA PEDIDO:** BICO SPRAY - CO5 - 10 - 3/8" NPT - INOX 304